



Shandong Lianchuang Gaoke Automation Co., Ltd.

📍 Yanzhuang Industrial Park, Gangcheng District,
Jinan, Shandong Province, China

🌐 en.sdlegk.com

☎ 400-138-3099

📞 0086 15806535521

**Focus on industrial automation products development
and intelligent manufacturing**



Shandong Lianchuang Gaoke Automation Co., Ltd.



Catalogue

Company profile

- P 01 ----- About us
- P 03 ----- Lianchuang manufacturing
- P 05 ----- Lianchuang qualification
- P 06 ----- Lianchuang services

Product range

- P 09 ----- LP300A series book structure frequency converter
- P 11 ----- LC410 series general frequency converter
- P 13 ----- LC400G series Double display type frequency converter
- P 15 ----- LC630A series economical frequency converter
- P 17 ----- LC640 series Mini economical frequency converter
- P 19 ----- LC880 series fan&pump specific frequency converter
- P 21 ----- LP330 series Direct Torque Control frequency converter
- P 23 ----- LP300Q series special frequency converter for lifting
- P 25 ----- LC400T series 220V to 380V frequency converter
- P 27 ----- LG200A series cabinet frequency converter
- P 29 ----- LG300A series 690V cabinet frequency converter
- P 31 ----- LP300Y series PMSM specific frequency converter
- P 33 ----- LC330Z series spindle servo motor combination
- P 35 ----- LC65 series high protection IP54 frequency converter
- P 37 ----- LC520 series frequency converter for elevator
- P 38 ----- New and original PLC controller module
- P 39 ----- LCJ20 series Kitchen fan specific frequency converter
- P 40 ----- LF10 series Industrial fan specific frequency converter



About us

Shandong Lianchuang Gaoke Automation Co., Ltd. was established in 2014, and its' main products are industrial frequency converters and other industrial control products.

The company is a professional manufacturer of industrial automation control products which integrates research and development, production, sales, and service. It has fully independent intellectual property rights in industrial automation drive control technology. Relying on strong research and development strength, adopting internationally advanced current vector control technology, and combining years of application experience in automation control, the company has developed domestically leading high, medium, and low voltage inverters, servo controllers, specialized and non-standard customized products. Currently, the company has products of different specifications such as 220V, 380V, 690V, and 220 to 380V, which are widely used in industries such as electric power, petrochemical, steel, oil fields, chemical engineering, building materials, textiles, printing, plastics, machine tools, mining, and other industries.

The company covers an area of 37 acres and owns over 21000 square meters of factory buildings, which have been successfully settled in.



The company has internationally leading SMT production lines, wave soldering lines, automatic coating lines, assembly lines, complete machine prediction systems, PCBA detection systems, and on-load aging test devices.

Currently, there are 10 regional sales centers and transfer warehouses in Xi'an, Zhengzhou, Wuhan, Shenyang, Xinjiang, and other places nationwide, with a complete sales network layout and timely / effective service response to meet customers' needs. The company has passed the recognition of national "High-Tech Enterprise", "Jinan Specialized and Special New", "Provincial Specialized and Special New", and municipal "Gazelle Enterprise". We have successively received honorary titles such as the "Industrial Enterprise Contribution Award", "Advanced Enterprise in Scientific and Technological Innovation", "Excellent Innovation and Entrepreneurship Enterprise", "One Enterprise One Technology Research and Development Center", and passed various qualification certifications such as "ISO9001 Quality System Certification", "Intellectual Property Management System Certification", "CE Certification" for Export to EU, "Software Copyright Certification", and "Integration of Industrialization and Industrialization", Which has laid a solid foundation for the subsequent development of the company.



Lianchuang manufacturing

Lianchuang Gaoke Automation Co., Ltd. currently has 1600 square meters of administrative research and development buildings and 8700 square meters of independent industrial manufacturing bases, with a large number of automated production equipments and complete production lines for various accessories.

The workshop integrates circuit board mounting, plug-in, three proofing adhesive coating, assembly, testing, sheet metal, and heat sink production line. Large, medium, and small power assembly lines are assembled in sections, with simplified procedures and efficient operation to ensure production capacity supply.



Focus on industrial automation products development
and intelligent manufacturing



Company qualification

Lianchuang adheres to the service philosophy of "seeking truth and pragmatism, exploring and innovating, intelligent driving, and scientific management", strictly controls product quality, and has won the recognition of society and customers in the highly competitive market.



Corporate Services

The Lianchuang Service Department has a group of senior frequency converter technical engineers, providing users with professional and fast solutions and technical support. The maintenance centers covering major cities across the country constitute a complete service network and a strong service team.

24 h
online

30 min
call

120 min
Provide solutions



Product line



LP300A Series
Book structure
frequency converter



LC410 Series
High performance
vector frequency converter



LC630A Series
Economical
frequency converter



LC640 Series
Mini economical
frequency converter



LP330 Series
DTC frequency
converter



LC880 Series
Fans & pumps
frequency converter



LC520 Series
Frequency converter
for elevator



PLC Series



LP300Q Series
Frequency converter
for lifting



LC400T Series
200V to 380V
frequency converter



LC400G Series
Double display
frequency converter



LG300A Series
690V cabinet
frequency converter



LP300Y Series
PMSM frequency
converter



LC65 Series
IP65
frequency converter



LCJ20 Series
Frequency converter
for kitchen fan



LF10 Series
Frequency converter
for Industrial fan

LP300A SERIES

Book structure high-performance
vector frequency converter



Product overview

The LP300A series uses a DSP control system as a platform, adopts current vector control technology, and cooperates with various protection methods. It can be applied to asynchronous motors to provide excellent driving performance. The product has greatly improved customer usability and environmental adaptability in terms of air duct design, hardware configuration, and software functions. Key components are all made from international brands such as TI, ON, and INFINEON to ensure customer experience.

Capacity range

3PH AC 380V±15%
1.5-400kw

Application area

CNC machine tools, textile machinery, roots blower, lifting, plastic machinery, food machinery, petroleum

Product features

- Book structure design, Modular structure layout ,volume is Max.60% reduced .
- High wind speed design scheme ,High protection reliability structure design
- Higher sealing degree of electronic components
- Stable and reliable performance, support double-row display, and strong adaptability
- Upper and lower straight air duct ,Wide tooth surface heat dissipation structure
- High drive torque characteristics, keep mechanical torque limit .
- EMC protection built in
- PG card expandable for close loop control.
- Powerful and supports multiple field buses
- Standard 485 communication, Can Link expandable.
- Support user programmable control card (PLC card), and the programming method is fully compatible with H1U series PLC

Specification and model	Rated output current(A)	Adaptive motor power(kw)	Height(H) Width(W) Depth(D) (mm)	Note
LP300A-1R5G/2R2P	3.8/5.1	1.5/2.2	200*86*183	Built in brake unit
LP300A-2R2G/4P	5.1/9	2.2/4		
LP300A-4G/5R5P	9/13	4/5.5	238*97*183	
LP300A-5R5G/7R5P	13/17	5.5/7.5		
LP300A-7R5G/11P	17/25	7.5/11	320*116*208	
LP300A-11G/15P	25/32	11/15		
LP300A-15G/18R5P	32/37	15/18.5	383*142*255	
LP300A-18R5G/22P	37/45	18.5/22		
LP300A-22G/30P	45/60	22/30	440*200*229	
LP300A-30G/37P	60/75	30/37		
LP300A-37G/45P	75/91	37/45	575*270*316	Optional built-in brake unit
LP300A-45G/55P	91/112	45/55		
LP300A-55G/75P	112/150	55/75	745*325*349	
LP300A-75G/90P	150/176	75/90		
LP300A-90G/110P	176/210	90/110	825*375*369	
LP300A-110G/132P	210/253	110/132		
LP300A-132G/160P	253/304	132/160	900*440*369	
LP300A-160G/185P	304/340	160/185		
LP300A-185G/200P	340/377	185/200	1025*526*369	
LP300A-200G/220P	377/415	200/220		
LP300A-220G/250P	415/465	220/250	1000*608*369	
LP300A-250G/280P	465/520	250/280		
LP300A-280G/315P	520/585	280/315	1000*608*369	
LP300A-315G/355P	585/650	315/355		
LP300A-355G/400P	650/725	355/400	1000*608*369	
LP300A-400G/450P	725/820	400/450		
Note : LP300A series panel opening size: 133.5mm high and 87.5mm wide				

LC410 SERIES

High performance vector frequency converter



Product overview

LC410 model is an upgrade model of LC400. Based on DSP control system, adopt current vector control technology and cooperate with various protection methods. It supports double line screen display, main components used are all made of international brands. The excellent hardware configuration and mature software installed have been proven to be secure and stable by thousands of clients.

Capacity range

3PH AC 380V $\pm$ 15%
1.5-500kw

Application area

CNC machine tools, forging machine tools, textile machinery, Roots blower, lifting and lifting, plastic machinery, petroleum, food machinery

Product features

- Upgrade version of LC400. Universal frequency converter, covering more than 90% applications
- Double line Screen panel appearance. Panel Removable
- Perfect software and hardware protection function. The output frequency can reach to 500Hz, solved the traditional gear limit problem
- Powerful current vector control performance, low noise, excellent energy-saving effect
- Speed tracking, Instantaneous stop, 0.1S acceleration and deceleration, 22G and below are with built-in brake unit
- 47 kinds of fault detection protection are set to effectively ensure the stable and reliable operation of the system
- Extensive expansion card options
- Powerful and supports multiple field buses
- Support asynchronous motor control
- Support user programmable control card (PLC card), and the programming method is fully compatible with H1U series PLC

Specification and model	Rated output current(A)	Adaptive motor power(kw)	Height(H) Width(W) Depth(D) (mm)
LC410-1R5G/2R2P-4T	3.8/5.1	1.5/2.2	186*125*180
LC410-2R2G/4R0P-4T	5.1/9	2.2/4	
LC410-4GS/5R5P-4T	9/13	4/5.5	
LC410-4G/5R5P-4T	9/13	4/5.5	249*161*199
LC410-5R5G/7R5P-4T	13/17	5.5/7.5	
LC410-7R5G/11P-4T	17/25	7.5/11	
LC410-11GS/15P-4T	25/32	11/15	321*208*200
LC410-11G/15P-4T	25/32	11/15	
LC410-15G/18R5P-4T	32/37	15/18.5	
LC410-18R5G/22P-4T	37/45	18.5/22	463*286*237
LC410-22G/30P-4T	45/60	22/30	
LC410-30G/37P-4T	60/75	30/37	
LC410-37G/45P-4T	75/91	37/45	600*386*277
LC410-45G/55P-4T	91/112	45/55	
LC410-55G/75P-4T	112/150	55/75	
LC410-75G/90P-4T	150/176	75/90	700*475*321
LC410-90G/110P-4T	176/210	90/100	
LC410-110G/132P-4T	210/253	100/132	
LC410-132G/160P-4T	253/304	132/160	930*580*387
LC410-160G/185P-4T	304/340	160/185	
LC410-185G/200P-4T	340/377	185/200	
LC410-200G/220P-4T	377/426	200/220	1060*650*386
LC410-220G/250P-4T	426/465	220/250	
LC410-250G/280P-4T	465/520	250/280	
LC410-280G/315P-4T	520/585	280/315	1358*800*399
LC410-315G/355P-4T	585/650	315/355	
LC410-355G/400P-4T	650/725	355/400	
LC410-400G/450P-4T	725/820	400/450	1175*840*410
LC410-450G/500P-4T	820/860	450/500	
LC410-500G/550P-4T	860/950	500/550	

Note : LP410 series panel opening size: 90mm high and 82mm wide

LC400G SERIES

Double display type frequency converter



Product overview

LC400G model is an upgrade model of LC400 display panel. Double line screen panel appearance. Based on DSP control system, adopt current vector control technology and cooperate with various protection methods. The excellent hardware configuration and mature software installed have been proven to be secure and stable by thousands of clients.

Capacity range

3PH AC 380V $\pm$ 15%
1.5-500kw

Application area

CNC machine tools, Forging Machine, textile machinery, Roots Blower Lifting, Plastic machinery, petroleum, Food machinery, etc.

Product features

- Double line Screen panel appearance. Panel Removable
- Universal frequency converter, covering more than 90% applications
- Perfect software and hardware protection function. The output frequency can reach to 500Hz, solved the traditional gear limit problem
- Powerful current vector control performance, low noise, excellent energy-saving effect
- Speed tracking, Instantaneous stop, 0.1S acceleration and deceleration, 22G and below are with built-in brake unit
- 47 kinds of fault detection protection are set to effectively ensure the stable and reliable operation of the system
- Extensive expansion card options
- Powerful and supports multiple field buses
- Support asynchronous motor control
- Support user programmable control card (PLC card), and the programming method is fully compatible with H1U series PLC

Specification and model	Rated output current(A)	Adaptive motor power(kw)	Height(H) Width(W) Depth(D) (mm)
LC400G-1R5G/2R2P-4T	3.8/5.1	1.5/2.2	186*125*180
LC400G-2R2G/4R0P-4T	5.1/9	2.2/4	
LC400G-4GS/5R5P-4T	9/13	4/5.5	
LC400G-4G/5R5P-4T	9/13	4/5.5	249*161*199
LC400G-5R5G/7R5P-4T	13/17	5.5/7.5	
LC400G-7R5G/11P-4T	17/25	7.5/11	
LC400G-11GS/15P-4T	25/32	11/15	321*208*200
LC400G-11G/15P-4T	25/32	11/15	
LC400G-15G/18R5P-4T	32/37	15/18.5	
LC400G-18R5G/22P-4T	37/45	18.5/22	463*286*247
LC400G-22G/30P-4T	45/60	22/30	
LC400G-30G/37P-4T	60/75	30/37	
LC400G-37G/45P-4T	75/91	37/45	600*386*277
LC400G-45G/55P-4T	91/112	45/55	
LC400G-55G/75P-4T	112/150	55/75	
LC400G-75G/90P-4T	150/176	75/90	700*475*321
LC400G-90G/110P-4T	176/210	90/100	
LC400G-110G/132P-4T	210/253	100/132	
LC400G-132G/160P-4T	253/304	132/160	930*580*387
LC400G-160G/185P-4T	304/340	160/185	
LC400G-185G/200P-4T	340/377	185/200	
LC400G-200G/220P-4T	377/426	200/220	1060*650*386
LC400G-220G/250P-4T	426/465	220/250	
LC400G-250G/280P-4T	465/520	250/280	
LC400G-280G/315P-4T	520/585	280/315	1358*800*399
LC400G-315G/355P-4T	585/650	315/355	
LC400G-355G/400P-4T	650/725	355/400	
LC400G-400G/450P-4T	725/820	400/450	1175*840*410
LC400G-450G/500P-4T	820/860	450/500	
LC400G-500G/550P-4T	860/950	500/550	

Note : LP400G series panel opening size: 147mm high and 79mm wide

LC630A SERIES

Economical vector frequency converter



Product overview

The LC630A series frequency converter is a general purpose high performance model for controlling small power Ac Asynchronous motors.the configuration of hardware is designed to be on economic basis but with strong power.It's a most popular model for economic frequency converters due to the good performance and low price.

Capacity range

3PH 380V±15%	1PH 220V±15%
0.75-22kw	0.4-7.5kw
1PH 110V±15%	
1.5kw	

Application area

Textile, paper making, wire drawing machines, packaging, food, fans, water pumps

Product features

- 110V input 1.5KW available
- 220V input 0.4-7.5KW available
- 380V input 0.75-22KW available.
- Compact good design
- Good dynamic performance
- Super overload capacity
- Rich combination functions
- 485 communication available
- Stable performance

Specification and model	Rated output current(A)	Adaptive motor power(kw)	Height(H) Width(W) Depth(D) (mm)
1PH AC 110V±15%			
LC630A-1R5G-1T	9	1.5	245*125*170
1PH AC 220V±15%			
LC630A-0R4G/0R75P-2T	2.3/4	0.4/0.75	170*85*138
LC630A-0R75G/1R5P-2T	4/7	0.75/1.5	
LC630A-1R5G/2R2P-2T	7/9.6	1.5/2.2	
LC630A-2R2G/4P-2T	9.6/17	2.2/4	245*125*170
LC630A-4G/5R5P-2T	17/24	4/5.5	
LC630A-5R5G/7R5P-2T	24/30	5.5/7.5	
LC630A-7R5G/11P-2T	30/40	7.5/11	310*165*198
3PH AC 380V±15%			
LC630A-0R75G/1R5P-4T	2.5/4.2	0.75/1.5	170*85*138
LC630A-1R5G/2R2P-4T	4.2/5.8	1.5/2.2	
LC630A-2R2G/4P-4T	5.8/10	2.2/4	
LC630A-4G/5R5P-4T	10/13	4/5.5	194*97*151
LC630A-5R5G/7R5P-4T	13/17	5.5/7.5	
LC630A-7R5G/11P-4T	17/25	7.5/11	245*125*170
LC630A-11G/15P-4T	25/32	11/15	
LC630A-15G/18R5P-4T	32/37	15/18.5	310*165*198
LC630A-18R5G/22P-4T	37/45	18.5/22	
LC630A-22G/30P-4T	45/60	22/30	

Note : LC630A series panel opening size: 115mm high and 85mm wide

LC640 SERIES

Mini economical vector frequency converter



Product overview

The LC640 series frequency converter is a newly designed model to satisfy simple task but strong performance required applications. The volume is small and configurations are based on economic basis. The constant pressure water supply function makes it widely used in water pump applications.

Capacity range

3PH 380V±15%	1PH 220V±15%
0.75-15kw	0.75-2.2kw

Application area

Textile, paper making, wire drawing machines, packaging, food, fans, water pump

Product features

- Single Phase AC 220V ±15% and three phase AC 380V±15% available
- Mini type. Most Economic design at very competitive price
- Compact design
- Constant pressure water supply function
- RS485 communication
- Good dynamic performance
- Super overload capacity
- Rich combination functions
- Stable performance



Specification and model	Rated output current(A)	Adaptive motor power(kw)	Height(H) Width(W) Depth(D) (mm)
1PH AC 220V±15%			
LC640-0R75G-2T	4	0.75	142*72*105.5
LC640-1R5G-2T	7	1.5	
LC640-2R2G-2T	9.6	2.2	
3PH AC 380V±15%			
LC640-0R75G-4T	2.1	0.75	142*72*105.5
LC640-1R5G-4T	3.8	1.5	
LC640-2R2G-4T	5.1	2.2	
LC640-4G-4T	9	4	181.5*87*127.5
LC640-5R5G-4T	13	5.5	
LC640-7R5G-4T	17	7.5	240*118*155
LC640-11G-4T	25	11	
LC640-15G-4T	32	15	
Note : LC640 series panel opening size: 75.4mm high and 49.4mm wide			



External keyboard

Opening size 75.4mm high and 49.4mm wide



LC880 SERIES

Fans and pumps vector frequency converter



Product overview

The 880 series inverter is the latest current vector inverter developed by our company, which improves low-speed torque and response speed. In terms of software capabilities, it improves the functions of automatic tuning, automatic control, online conversion, and speed tracking of motor parameters. Built-in PID controller and simple PLC. Various fault monitoring and rich terminal configurations meet various industrial transmission requirements.

Capacity range

3PH AC 380V±15%
1.5-200kw

Application area

Food machinery, woodworking machinery, packaging machinery, fans and pumps

Product features

- Special purpose of Water Pumps and Fans
- MPPT setting, Solar Pump Watering Mode
- Powerful PID adjustment function, removable control panel, convenient for using.
- Built in multiple water supply application macros
- Stepless speed regulation leaves the traditional gear limit, and 0-500Hz can be adjusted arbitrarily
- Powerful current vector control performance, low noise, excellent energy-saving effect
- 485 communication interface, supporting MODBUS international standard communication protocol

Specification and model	Rated output current(A)	Adaptive motor power(kw)	Height(H) Width(W) Depth(D) (mm)
LC880-1R5G/2R2P	3.8/5.1	1.5/2.2	212*95*158
LC880-2R2G/4P	5.1/8.5	2.2/4	
LC880-4G/5R5P	8.5/13	4/5.5	
LC880-5R5G/7R5P	13/16	5.5/7.5	
LC880-7R5G/11P	16/24	7.5/11	240*140*188
LC880-11G/15P	24/32	11/15	
LC880-15G/18R5P	32/36	15/18.5	
LC880-18R5G/22P	36/45	18.5/22	323*205*208
LC880-22G/30P	45/60	22/30	
LC880-30G/37P	60/75	30/37	
LC880-37G/45P	75/91	37/45	
LC880-45G/55P	91/112	45/55	490*270.5*215
LC880-55G/75P	112/150	55/75	
LC880-75G/90P	150/176	75/90	620*340*304
LC880-90G/110P	176/210	90/110	
LC880-110G/132P	210/253	110/132	
LC880-132G/160P	253/304	132/160	660*400*323
LC880-160G/185P	304/340	160/185	
LC880-185G/200P	340/377	185/200	780*530*354
LC880-200G/220P	377/426	200/220	

Note : LP880 series panel opening size: 90mm high and 82mm wide

LP330 SERIES

Direct torque control frequency converter
(LCD Display)



Product Overview

The LP330 series has significantly improved usability, maintainability, environmental friendliness, installation space, and design standards from a customer perspective while maintaining excellent basic performance and functionality. High standard design in the industry, based on years of persistent pursuit of driving technology and accumulated experience in multiple industry applications, continuously leading the industry; High performance, high quality, high power density design, more in line with the user's personal experience.

Capacity range

3PH AC 380V±15%
1.5-400kw

Application area

CNC machine tools, textile machinery, roots blower, lifting, plastic machinery, food machinery, petroleum

Product features

- LCD Display, switch for AC Induction Motor and PMSM motor.
- The industry first promotes IGBT junction temperature real-time monitoring technology, accurately calculating IGBT junction temperature and effectively protecting IGBT
- The sealed design of the entire machine with independent heat dissipation ducts reduces the impact of harsh environments on electronic devices
- The industry is the first to promote full product heavy-duty (120% rated load) high temperature (50 °C) aging testing and inspection, strictly ensuring product quality.



Specification and model	Rated output current(A)	Adaptive motor power(kw)	Height(H) Width(W) Depth(D) (mm)	Note	
LP330-1R5G/2R2P	3.8/5.1	1.5/2.2	200*86*183	Built in brake unit	
LP330-2R2G/4P	5.1/9	2.2/4			
LP330-4G/5R5P	9/13	4/5.5	238*97*183		
LP330-5R5G/7R5P	13/17	5.5/7.5			
LP330-7R5G/11P	17/25	7.5/11	320*116*208		
LP330-11G/15P	25/32	11/15			
LP330-15G/18R5P	32/37	15/18.5	383*142*255		
LP330-18R5G/22P	37/45	18.5/22			
LP330-22G/30P	45/60	22/30			
LP330-30G/37P	60/75	30/37	440*200*229		
LP330-37G/45P	75/91	37/45			
LP330-45G/55P	91/112	45/55	575*270*316	Optional built-in brake unit	
LP330-55G/75P	112/150	55/75			
LP330-75G/90P	150/176	75/90			
LP330-90G/110P	176/210	90/110	745*325*349		
LP330-110G/132P	210/253	110/132			
LP330-132G/160P	253/304	132/160			
LP330-160G/185P	304/340	160/185	825*375*369		
LP330-185G/200P	340/377	185/200	900*440*369		
LP330-200G/220P	377/415	200/220			
LP330-220G/250P	415/465	220/250			
LP330-250G/280P	465/520	250/280	1025*526*369		
LP330-280G/315P	520/585	280/315			
LP330-315G/355P	585/650	315/355			
LP330-355G/400P	650/725	355/400	1000*608*369		
LP330-400G/450P	725/820	400/450			
Note : LP330 series panel opening size: 133.5mm high and 87.5mm wide					

Note : LP330 series panel opening size: 133.5mm high and 87.5mm wide

LP300Q SERIES

Special frequency converter for lifting



Product overview

LP300Q is a crane specific frequency converter developed by our company, which can perform V/F control or vector control on AC asynchronous motors. It is suitable for crane equipment with high starting torque, simple debugging, and can achieve 16 speed operation, closed-loop process control, and networking functions of the system.

Capacity range

3PH AC 380V $\pm$ 15%
1.5-400kw

Application area

CNC machine tools, textile machinery, roots blower, lifting, plastic machinery, food machinery, petroleum

Product features

- Built in professional lifting specialized brake timing control. Ensure smooth start and stop of the load
- When the bus voltage continues to be low, reduce the given frequency of the load to maintain the normal output of the frequency converter, and avoid undervoltage faults during operation
- When the bus voltage momentarily decreases or there is a power outage, the frequency converter quickly stops and restricts the continuation to ensure that the hook does not slip
- Automatically calculate the highest achievable output frequency by detecting the output torque of the frequency converter

Specification and model	Rated output current(A)	Adaptive motor power(kw)	Height(H) Width(W) Depth(D) (mm)	Note
LP300Q-1R5G/2R2P	3.8/5.1	1.5/2.2	200*86*183	Built in brake unit
LP300Q-2R2G/4P	5.1/9	2.2/4		
LP300Q-4G/5R5P	9/13	4/5.5	238*97*183	
LP300Q-5R5G/7R5P	13/17	5.5/7.5		
LP300Q-7R5G/11P	17/25	7.5/11	320*116*208	
LP300Q-11G/15P	25/32	11/15		
LP300Q-15G/18R5P	32/37	15/18.5	383*142*255	
LP300Q-18R5G/22P	37/45	18.5/22		
LP300Q-22G/30P	45/60	22/30		
LP300Q-30G/37P	60/75	30/37	440*200*229	
LP300Q-37G/45P	75/91	37/45		
LP300Q-45G/55P	91/112	45/55	575*270*316	
LP300Q-55G/75P	112/150	55/75		
LP300Q-75G/90P	150/176	75/90		
LP300Q-90G/110P	176/210	90/110	745*325*349	
LP300Q-110G/132P	210/253	110/132		
LP300Q-132G/160P	253/304	132/160		
LP300Q-160G/185P	304/340	160/185	825*375*369	
LP300Q-185G/200P	340/377	185/200	900*440*369	
LP300Q-200G/220P	377/415	200/220		
LP300Q-220G/250P	415/465	220/250		
LP300Q-250G/280P	465/520	250/280	1025*526*369	
LP300Q-280G/315P	520/585	280/315		
LP300Q-315G/355P	585/650	315/355		
LP300Q-355G/400P	650/725	355/400	1000*608*369	
LP300Q-400G/450P	725/820	400/450		
Note : LP300Q series panel opening size: 133.5mm high and 87.5mm wide				

Note : LP300Q series panel opening size: 133.5mm high and 87.5mm wide

LC400T SERIES



1PH 220V input--3PH380V output
frequency converter



Product overview

LC400T series 220V to 380V frequency converters are specially developed by us for occasions where three-phase power is lacking. With multiple protection methods and excellent driving performance, they can solve the difficulty of users lacking 380V power. The wiring connecting is simple and easy to understand, and the operation is convenient and practical.

Capacity range

INPUT : 1PH AC 220V±15%
OUTPUT : 3PH AC 380V±15%
1.5-45kw

Application area

Paper making, wire drawing machines, textile machinery, packaging machinery, food machinery, fans and pumps

Product features

- Good hardware configuration and mature software installed proven to be secure and stable
- Good and stable performance
- Comprehensive protection functions
- Fast response speed, easy to control
- Excellent low-frequency counter output
- High control accuracy
- Convenient wiring

Specification and model	Rated output current(A)	Adaptive motor power(kw)	Height(H) Width(W) Depth(D) (mm)
LC400T-1R5G/2R2P	3.8/5.1	1.5/2.2	186*125*180
LC400T-2R2G/4R0P	5.1/9	2.2/4	
LC400T-4GS/5R5P	9/13	4/5.5	
LC400T-4G/5R5P	9/13	4/5.5	249*161*199
LC400T-5R5G/7R5P	13/17	5.5/7.5	
LC400T-7R5G/11P	17/25	7.5/11	
LC400T-11GS/15P	25/32	11/15	321*208*200
LC400T-11G/15P	25/32	11/15	
LC400T-15G/18R5P	32/37	15/18.5	
LC400T-18R5G/22P	37/45	18.5/22	463*286*237
LC400T-22G/30P	45/60	22/30	
LC400T-30G/37P	60/75	30/37	
LC400T-37G/45P	75/91	37/45	600*386*277
LC400T-45G/55P	91/112	45/55	

Note : LC400T series panel opening size: 147mm high and 79mm wide

LG200A SERIES



Cabinet type high-performance
vector frequency converter



Product overview

LG200A is the latest high-performance cabinet type vector frequency converter launched by our company in response to market demand. It can meet the requirements of various industries with high performance, high flexibility, simple operation, and complete functions. With dual digital tube display, it can meet the different needs of customers.

Capacity range

3PH AC 380V±15%
110-1000kw

Application area

Textile machinery, Roots blower, plastic machinery, petroleum, food machinery, paper making

Product features

- Imported IGBT Infineon Module, with strong carrying capacity and good stability
- Powerful current vector control performance, low noise and excellent energy-saving effect
- Standard built-in reactor, vertical cabinet design, independent air duct heat dissipation
- Humanized design, intelligent control, LED panel dual display, clear and intuitive
- Perfect multiple protection measures for over current, over voltage and lack of voltage
- RS485 serial communication interface, supporting MODBUS international standard communication protocol

Specification and model	Rated output current(A)	Adaptive motor power(kw)	Height(H) Width(W) Depth(D) (mm)	Note	
LG200A-110G/132P	210/253	110/132	830*380*335	Built in DC reactor	Incoming method: bottom in and bottom out
LG200A-132G/160P	253/304	132/160			
LG200A-160G/185P	304/340	160/185	1075*525*350		
LG200A-185G/200P	340/377	185/200			
LG200A-200G/220P	377/426	200/220			
LG200A-220G/250P	426/465	220/250			
LG200A-250G/280P	465/520	250/280	1150*555*355		
LG200A-280G/315P	520/585	280/315			
LG200A-315G/355P	585/650	315/355			
LG200A-355G/400P	650/725	355/400	1450*650*390		
LG200A-400G/450P	725/820	400/450			
LG200A-450G/500P	820/860	450/500			
LG200A-500G/560P	860/950	500/560	1600*750*500		
LG200A-560G/630P	950/1100	560/630			
LG200A-630G/710P	1100/1250	630/710	1801.5*797*700	Built in AC reactor	
LG200A-710G/750P	1250/1379	710/750			
LG200A-750G/800P	1379/1420	750/800	1851.5*997*800	Built in DC reactor	
LG200A-800G/900P	1420/1610	800/900			
LG200A-900G/1000P	1610/1790	900/1000			
LG200A-1000G/1100P	1790/1960	1000/1100			
Note : LG200A series panel opening size: 133.5mm high and 87.5mm wide					

Note : LG200A series panel opening size: 133.5mm high and 87.5mm wide

LG300A SERIES



690V Input Cabinet Type Strong Power
Vector Frequency Converter



Product overview

LG300A is an upgrade high power model of LG200A with 690V voltage input. The main spare parts used are mostly famous brand imported to guarantee the durable performance. The cabinet design and strong powerful performance can satisfy those applications with higher demanding.

Capacity range

3PH AC 690V $\pm$ 15%
45-1200kw

Application area

Textile machinery, Roots blower, plastic machinery, petroleum, food machinery, paper making

Product features

- 690V Input Voltage
- Power from 45kw-1200kw available
- Imported IGBT Infineon Module, with strong carrying capacity and good stability.
- Powerful current vector control performance, low noise and excellent energy-saving effect.
- Standard built-in reactor, vertical cabinet design, independent air duct heat dissipation.
- Humanized design, intelligent control, LED panel dual display, clear and intuitive.
- Perfect multiple protection measures for over current, over voltage and lack of voltage.
- RS485 serial communication interface, supporting MODBUS international standard communication protocol

Specification and model	Rated output current(A)	Adaptive motor power(kw)	Height(H) Width(W) Depth(D) (mm)	Note	
LG300A-45G/55P	50/65	45/55	655*270*315		
LG300A-55G/75P	65/86	55/75			
LG300A-75G/90P	86/100	75/90			
LG300A-90G/110P	100/120	90/110	745*325*350		
LG300A-110G/132P	120/150	110/132			
LG300A-132G/160P	150/175	132/160	830*380*335		
LG300A-160G/200P	175/215	160/200			
LG300A-200G/220P	215/245	200/220	1025*525*350	Built in DC reactor	
LG300A-220G/250P	245/260	220/250			
LG300A-250G/280P	260/299	250/280			
LG300A-280G/315P	299/330	280/315			
LG300A-315G/355P	330/374	315/355	1150*555*355		
LG300A-355G/400P	374/410	355/400			
LG300A-400G/450P	410/465	400/450	1450*650*390		
LG300A-450G/500P	465/550	450/500			
LG300A-500G/560P	550/575	500/560			
LG300A-560G/630P	575/680	560/630	1600*750*500		
LG300A-630G/710P	680/712	630/710			
LG300A-710G/800P	712/802	710/800			
LG300A-800G/900P	802/897	800/900			
LG300A-900G/1000P	897/1008	900/1000	1855*1000*800		
LG300A-1000G/1100P	1008/1164	1000/1100			
LG300A-1100G/1200P	1164/1201	1100/1200			
LG300A-1200G/1300P	1201/1310	1200/1300			
Note : LG300A series panel opening size: 133.5mm high and 87.5mm wide					

Note : LG300A series panel opening size: 133.5mm high and 87.5mm wide

LP300Y SERIES

Special frequency converter for
permanent magnet synchronous motor



Product overview

The LP300Y series permanent magnet synchronous controller is mainly used to control and adjust the speed and torque of permanent magnet synchronous motors, and is a technology upgrade product of the LP300 series. LP300Y adopts high-performance vector control technology, with low speed and high torque output, good dynamic characteristics, strong overload capacity, added user programmable function and background monitoring software, communication bus function, support for multiple PG cards, etc. The combination function is rich and powerful, with stable performance, and can be used for driving various automated production equipment.

Capacity range

3PH AC 380V±15%
1.5-400kw

Application area

CNC machine tools, textile machinery, roots blower, lifting, plastic machinery, food machinery, petroleum

Product features

- Suitable for permanent magnet synchronous motor drive control
- High accuracy of self tuning motor parameters
- High stability accuracy and wide speed range
- Low speed with high torque and low torque ripple
- Can achieve complete V/F separation and semi separation
- Can achieve open loop and closed-loop control
- Supports multiple PG cards
- Standard RS485 communication interface



Specification and model	Rated output current(A)	Adaptive motor power(kw)	Height(H) Width(W) Depth(D) (mm)	Note	
LP300Y-1R5G/2R2P	3.8/5.1	1.5/2.2	200*86*183	Built in brake unit	
LP300Y-2R2G/4P	5.1/9	2.2/4			
LP300Y-4G/5R5P	9/13	4/5.5	238*97*183		
LP300Y-5R5G/7R5P	13/17	5.5/7.5			
LP300Y-7R5G/11P	17/25	7.5/11	320*116*208		
LP300Y-11G/15P	25/32	11/15			
LP300Y-15G/18R5P	32/37	15/18.5	383*142*255		
LP300Y-18R5G/22P	37/45	18.5/22			
LP300Y-22G/30P	45/60	22/30	440*200*229		
LP300Y-30G/37P	60/75	30/37			
LP300Y-37G/45P	75/91	37/45	575*270*316	Optional built-in brake unit	
LP300Y-45G/55P	91/112	45/55			
LP300Y-55G/75P	112/150	55/75			
LP300Y-75G/90P	150/176	75/90			
LP300Y-90G/110P	176/210	90/110			745*325*349
LP300Y-110G/132P	210/253	110/132			
LP300Y-132G/160P	253/304	132/160			
LP300Y-160G/185P	304/340	160/185	825*375*369		
LP300Y-185G/200P	340/377	185/200	900*440*369		
LP300Y-200G/220P	377/415	200/220			
LP300Y-220G/250P	415/465	220/250			
LP300Y-250G/280P	465/520	250/280	1025*526*369		
LP300Y-280G/315P	520/585	280/315			
LP300Y-315G/355P	585/650	315/355			
LP300Y-355G/400P	650/725	355/400	1000*608*369		
LP300Y-400G/450P	725/820	400/450			
Note : LP300Y series panel opening size: 133.5mm high and 87.5mm wide					

Note : LP300Y series panel opening size: 133.5mm high and 87.5mm wide

LP330Z SERIES

Spindle servo motor combination



Product Overview

The LP330Z spindle servo motor set is a specialized servo driver developed for the characteristics of the high-speed machining machine tool industry. The spindle servo driver supports high-speed permanent magnet synchronous servo spindles, which can achieve precise dynamic response control and meet the process requirements of drilling, grinding, engraving and milling, and turning and milling composite. It integrates high-speed command input and feedback output interfaces, which can be combined with mainstream controllers in the market to form machine tool electronic control systems, and can also be seamlessly linked with CNC systems with open architecture.

Capacity range

3PH AC 380V±15%
1.5-75kw

Application area

CNC machine tools, machining centers, and mechanical equipment that requires positioning

Product features

- Full closed-loop control of current, speed, and position.
- Adopting multi degree of freedom and nonlinear control algorithms to achieve high dynamic response and high-precision current, speed, and position control.
- Supports high-speed pulse+directional input, with analog, network, and control interfaces.
- Supports high-precision sine and cosine encoders, rotary transformer speed feedback, with a single turn resolution of up to 24 bits.
- Supports high-speed local IO and remote expansion IO.



Specification and model	Rated output current(A)	Adaptive motor power(kw)	Height(H) Width(W) Depth(D) (mm)	Note
LP330Z-1R5G/2R2P	3.8/5.1	1.5/2.2	200*86*183	Built in brake unit
LP330Z-2R2G/4P	5.1/9	2.2/4		
LP330Z-4G/5R5P	9/13	4/5.5	238*97*183	
LP330Z-5R5G/7R5P	13/17	5.5/7.5		
LP330Z-7R5G/11P	17/25	7.5/11	320*116*208	
LP330Z-11G/15P	25/32	11/15		
LP330Z-15G/18R5P	32/37	15/18.5	383*142*255	
LP330Z-18R5G/22P	37/45	18.5/22		
LP330Z-22G/30P	45/60	22/30		
LP330Z-30G/37P	60/75	30/37	440*200*229	
LP330Z-37G/45P	75/91	37/45		
LP330Z-45G/55P	91/112	45/55	575*270*316	Optional built-in brake unit
LP330Z-55G/75P	112/150	55/75		
LP330Z-75G/90P	150/176	75/90		
Note : LP330Z series panel opening size: 133.5mm high and 87.5mm wide				

Note : LP330Z series panel opening size: 133.5mm high and 87.5mm wide

LC65 SERIES

IP65 High-protection level advanced frequency converter



Product overview

The LC65 series high protection level frequency converter reaches IP65 protection level, and the PCB adopts industrial high protection level UV coating to enhance resistance. Specially designed for harsh environments such as high corrosion, high dust, high humidity, high temperature, and heavy pollution, it is sturdy, durable, and highly protective.

Capacity range

3PH 380V±15%
1.5-315kw

Application area

CNC machine tools, textile machinery, roots blower, lifting, plastic machinery, food machinery, petroleum

Product features

- Fully enclosed chassis design, using three anti paint, waterproof joints, waterproof fans, etc., waterproof, dustproof, oil stain resistant, corrosion-resistant, suitable for use in harsh environments
- Equipped with various motor protection functions
- Smooth operation, low noise, and excellent energy-saving effect
- Standard RS485 communication interface



Specification and model	Rated output current(A)	Adaptive motor power(kw)	Height(H) Width(W) Depth(D) (mm)
LC65-0R75G/1R5P-4T	2.1/3.8	0.75/1.5	255*160*184
LC65-1R5G/2R2P-4T	3.8/5.1	1.5/2.2	
LC65-2R2G/4P-4T	5.1/9.0	2.2/4	
LC65-4G/5R5P-4T	9.0/13	4/5.5	305*200*181
LC65-5R5G/7R5P-4T	13/17	5.5/7.5	
LC65-7R5G/11P-4T	17/25	7.5/11	
LC65-11G/15P-4T	25/32	11/15	380*223*204
LC65-15G/18R5P-4T	32/37	15/18.5	
LC65-18R5G/22P-4T	37/45	18.5/22	
LC65-22G/30P-4T	45/60	22/30	483*316*224
LC65-30G/37P-4T	60/75	30/37	
LC65-37G/45P-4T	75/91	37/45	
LC65-45G/55P-4T	91/112	45/55	600*386*264
LC65-55G/75P-4T	112/150	55/75	
LC65-75G/90P-4T	150/176	75/90	
LC65-90G/110P-4T	176/210	90/110	700*475*307
LC65-110G/132P-4T	210/253	110/132	
LC65-132G/160P-4T	253/304	132/160	
LC65-160G/185P-4T	304/340	160/185	930*580*374
LC65-185G/200P-4T	340/377	185/200	
LC65-200G/220P-4T	377/426	200/220	
LC65-220G/250P-4T	426/465	220/250	1060*650*375
LC65-250G/280P-4T	465/520	250/280	
LC65-280G/315P-4T	520/585	280/315	

Note : LC65 series panel opening size: 147mm high and 79mm wide

LC520 SERIES

Frequency Converter for Elevator



Capacity range

3PH AC 380V $\pm$ 15%
7.5-18.5kw

Application area

Elevator control

Product features

- Suitable for driving control of permanent magnet synchronous motors and asynchronous motors, with multiple rotary encoder interfaces.
- Equipped with motor parameter self-tuning function, it can perform static tuning or complete tuning.
- Support multi segment speed and analog speed setting.
- Flexible start curve processing, multi segment S curve setting, and 4-level acceleration and deceleration time setting can ensure good elevator operation comfort. It has a simple and practical battery operation function, and can complete power outage self rescue with a 48V power input.
- It has various elevator specific functions such as enabling detection, holding brake contactor control, output contactor control, forced deceleration judgment, overspeed protection, speed deviation detection, early door opening, contact adhesion detection, motor overheating detection, starting pre torque compensation, etc., making elevator control simple and feasible.

Specification and model	Rated input current(A)	Rated output current(A)	Height(H) Width(W) Depth(D) (mm)
LC520-7.5KW	20.5	18	248*160*183
LC520-11KW	29	27	322*208*192
LC520-15KW	36	33	
LC520-18.5KW	41	39	

PLC SERIES

New and Original PLC Controller Module



Product overview

The SR/ST CPU module integrates one Ethernet interface and one RS485 interface. By expanding the CM01 signal board or EM DP01 module, the number of communication ports can be increased to a maximum of four, which can meet the communication needs of small automation equipment with touch screens, frequency converters, and other third-party devices.

Application area

Labeling machinery, Pillow packing machinery, Woodworking machinery etc.

Product features

- Rich models with more choices
- Option extension, precise customization
- High speed chip with excellent performance
- Ethernet connectivity, economic convenience
- Three axis pulse, free to move
- Universal SD card for quick updates
- Software friendly, programming efficient
- Perfect integration, seamless integration

Model	SR20	SR30	SR40	SR60
On-board digital I/O	12 Input/8 Output	18 Input/12 Output	24 Input/16 Output	36 Input/24 Output
High speed counting	6 Routes			
High speed pulse output	-			
Number of communication ports	2~4			
Expand the number of horizontal blocks	6			
Number of expansion signal boards	1			
Maximum switch quantity I/O	216	226	236	256
Maximum analog I/O	49			

LCJ20 SERIES

Kitchen Fan Specific Frequency Converter



Capacity range

3PH AC 380V±15%
4-22kw

Application area

Kitchen fan

Product features

- Stainless steel wire drawing box, enhancing overall aesthetics
- Smooth start stop reduces wear and tear
- Eliminate motor electromagnetic noise and reduce system noise
- Multiple protections such as missing items, short circuits, overload, insulation damage, etc
- Tailored for the kitchen, more suitable and economical
- Touch screen design, intelligent energy-saving of 20%, more technological and intelligent
- Intelligent mute, quieter, more comfortable, and more environmentally friendly



Specification and model	Rated output current(A)	Adaptive motor power(kw)	Height(H) Width(W) Depth(D) (mm)
LCJ20-4KW	9.5	4	500*300*186
LCJ20-5.5KW	13	5.5	
LCJ20-7.5KW	17	7.5	
LCJ20-11KW	25	11	
LCJ20-15KW	32	15	
LCJ20-18.5KW	38	18.5	
LCJ20-22KW	46	22	

LF10 SERIES

Permanent Magnet Industrial Fan Specific Frequency Converter



Capacity range

3PH AC 380V±15% 1PH AC 220V±15%
0.75-2.2kw 0.75-1.5kw

Application area

Industrial fan

Product features

- The motor starts and stops smoothly, running smoothly
- Reduce power consumption and reduce full load current
- Reduce the temperature rise of the motor
- Quiet, comfortable, and low noise.



Specification and model	Rated output current(A)	Input parameter	Output parameter	Height(H) Depth(D)	Width(W) (mm)
1PH AC 220V±15%					
LF10-0.75KW-2T	0.75	50/60Hz	4A, 0-300Hz	196.5*110.5*76.5	
LF10-1.5KW-2T	1.5	50/60Hz	7A, 0-300Hz		
3PH AC 380V±15%					
LF10-0.75KW-4T	0.75	50/60Hz	2.1A, 0-300Hz	265*170*131	
LF10-1.5KW-4T	1.5	50/60Hz	3.8A, 0-300Hz		
LF10-2.2KW-4T	2.2	50/60Hz	5.1A, 0-300Hz		

Application cases

